



Datasheet 6) : NGU Power Cell & 100W Basic Generator

	Product	NGU 10W Power Cell	NGU 100 W Basic Generator
	Model	SKL-NGU-10W	SKL-NGU-100W
	Design	High-Capacity Power Cell	Basic Generator from 10 Power Cells
	Application	Cost-Effective Stationary and Mobile 24/7 Sustainable Generation of Electricity	

Output Data

DC Voltage 1):	V_{set}	12 V +/- 1%	12 V
Rated Continuous Power	P_{max}	10 W	100 W
Operational Current 2)	I_{out}	Function of V_{set}	
Overload Protection 2)		Integrated AI control	
Serial & Parallel Connection		Max. serial voltage = 240 V	Options on request
AC Voltage Output		Options on request	

Energy Data

Power Capacity / Year 3)		87 kWh	870 kWh
Power Density [kW / liter]		0.12	0.12
Power Density [kW / kg]		0.33	0.4
Heat Dissipation		Less than 10 % of output power	
Grey Energy [%] 4)		Less than 0.1 %	
Warranty		3 years full = 26 280 operational hours	
Expected Lifetime		More than 100 000 operational hours	

Sustainability

Non Hazardous Class		Yes, with reference to the compliances below	
Electricity Generation 7)		E-Cat Technology with SSM	
Recycling		100 % of product content can be recirculated by the manufacturer	

General Data

Installation		Stationary Use - Horizontal mounting (0 degree) with max +/- 45-degree deviation	
Operating Temperature		- 20 °C to + 60 °C	
Case Design 5)		Cylinder from 3mm white Plexiglas	
Water Protection		Indoor Use - Other protection level on request	
Isolation Design		IEC 60112	
Dimensions		Cylindric: D = 60 mm, L= 30 mm	Cylindric: D = 60 mm, L= 300 mm
Weight [g]		30 g	250 g
DC Connection 5)		2 wires - 5 cm long	2 wires - 10 cm long

Compliances

Safety and EMC Compliances		EN 55015, 61457, 62493, 60598-1, 60598-2-1, 62031 EN IEC 61000-3-2, 61000-3-3
----------------------------	---	--

Remarks

- 1) Rated DC voltage V_{set} is by default factory set to 12 V.
- 2) $I_{out} = V_{set} / R_{load}$. Output is auto switched to OFF (0 V) when R_{load} is disconnected or $I_{out} > P_{max}/V_{set}$. Output is auto switched ON (V_{set}) when connected to R_{load} and $I_{out} = < P_{max}/V_{set}$. Reaction Time from OFF to ON is < 1 s
- 3) Maximal DC Power Generation [kWh] per year = $P_{max} * 365 * 24$ h
- 4) Share of potential energy generation during the estimated lifetime of > 100 000 hours
- 5) Alternative option available on customer request.
- 6) More detailed data available on request. See also white paper: "[E-Cat Power : The Impossible Made Possible](#)".
- 7) Self Sustained Mode (SSM) extraction of electricity from ZPE field, referenced publication: https://ecatthenewfire.com/wp-content/uploads/2025/08/ECatSK_and_Irpi2.4.pdf



Datasheet 6) : NGU Power Generators



Produkt	NGU 1kW	NGU 2kW	NGU 3kW	NGU 5kW	NGU 10kW	NGU MW Plant
Model	SKL-NGU-1K	SKL-NGU-2K	SKL-NGU-3K	SKL-NGU-5K	SKL-NGU-10K	SKL-NGU-1/2M
Design	Power Generators made from serial & parallel connection of multiple Basic 100W Generator					
Application	Cost-Effective Stationary and Mobile 24/7 Sustainable Generation of Electricity					

Output Data

DC Voltage :1) V_{set}	On request	On request	On request	On request	On request	On request
Rated Power P_{max}	1 kW	2 kW	3 kW	5 kW	10 kW	1 MW / 2 MW
Operational Current 2) I_{out}	Function of V_{set} ($I_{out} = V_{set} / R_{load}$) – details on request					
Serial & Parallel Connection	Depends on rated power and voltage – details on request					
AC Voltage Output	Option – details on request					

Energy Data

Power Capacity / Year 3)	8 300 kWh	16 600 kWh	24 900 kWh	41 600 kWh	83 000 kWh	830 /1 660 MWh
Power Density [kW / liter]	0.27	0.27	0.27	0.27	0.27	On request
Power Density [kW / kg]	0.5	0.67	0.75	0.83	0.91	On request
Heat Dissipation [%]	Less than 10 % of Output power					
Grey Energy [%] 4)	Less than 0.1 %					
Warranty	3 years full = 26 280 operational hours					
Expected Lifetime	More than 100 000 operational hours					

Sustainability

Non Hazardous Class	Yes, with reference to the compliances below					
Electricity Generation 7)	E-Cat Technology with SSM					
Recycling	100 % of product content can be recirculated by the manufacturer					

General Data

Installation	Stationary Use - Horizontal mounting (0 degree) with max + - 45-degree deviation					
Operating Temperature	- 20 °C to + 60 °C					
Case Design 5)	3mm white Plexiglas cover					On request
Water Protection	Indoor Use - Other protection level on request					
Isolation Design	IEC 60112					
Dimensions	25 x 15 x 10 cm	25 x 15 x 20 cm	25 x 15 x 30 cm	25 x 15 x 50 cm	25 x 15 x 100 cm	20 / 40 ft cont.
Weight [kg]	2 kg	3 kg	4 kg	6 kg	11 kg	On request
Volume [liter]	3.75	7.5	11.3	18.8	37.5	On request
DC Connection 5)	2 wire 100 cm cable					On request

Compliances

Safety and EMC Compliances	CE	EN 55015, 61457, 62493, 60598-1, 60598-2-1, 62031 EN IEC 61000-3-2, 61000-3-3				
----------------------------	----	--	--	--	--	--

Remarks

- V_{set} is factory set by the appropriate serial & parallel combination of the required number of the 12V/100W Basic generator. Possible values for V_{set} are available on request.
- $I_{out} = V_{set} / R_{load}$. Output is auto switched to OFF (0 V) when R_{load} is disconnected or $I_{out} > P_{max}/V_{set}$. Output is auto switched ON (V_{set}) when connected to R_{load} and $I_{out} < P_{max}/V_{set}$. Reaction Time from OFF to ON is < 1 s
- Maximal DC Power Generation [kWh] per year = $P_{max} * 365 * 24$ h
- Share of potential energy generation during the estimated lifetime of > 100 000 hours
- Alternative option available on customer request.
- More detailed data available on request.
See also white paper: "E-Cat Power : The Impossible Made Possible".
- Self Sustained Mode (SSM) extraction of electricity from ZPE field, referenced publication : https://ecatthenewfire.com/wp-content/uploads/2025/08/ECatSK_and_Irpi2.4.pdf

E-Cat Power NGU Datasheet - December 2024

This document is subject to change without notice. The latest version is found on <https://ecat.com>

E-Cat Power : 24/7 Unlimited Sustainable Electricity from Nature

is a product of **Leonardo Corporation 1331 Lincoln Miami Beach, Florida 33139, USA**

© All Rights Reserved Contact: info@leonardocorp1996.com